
Volumetric dividers









 \bigotimes

Built-in flour dispenser









SPECIFICATIONS

Adjustable speed in pieces per hour	960 - 2000
Teflon-coated hopper, capacity in kg	120
Programmable counter, countdown counter	
Stainless steel drum	
Triple-seal Rilsan piston	
Stainless steel exterior	
Outfeed belt width in mm	270
3-litre flour dispenser	
Outfeed belt scraper	
Oil recycling system	
Motor power in kW	2.2
Power supply	400V three-phase
Net weight in kg	525

TECHNICAL SPECIFICATIONS

Outfeed belt length in mm	1.060,1.240
Piston (Max/min weight of dough pieces in grams)	80mm (30 / 370),100mm (50 / 700),110mm (70 / 850),120mm (90 / 1.000),130mm (130 / 1.300)
Options (Additional cost)	160 kg capacity stainless-steel hopper, 200 kg capacity stainless-steel hopper, Automatic weight adjustment + dough piece counter, Outfeed belt with independent motor (automated production line version), Remote control, Extracting dough pieces device (*Standard on 80-mm and 100-mm pistons), Power supply 230V single phase, Power supply 230V three phase, Dough piece lubrication, Teflon-coated hopper, Dough piece counter

MAIN STRENGTHS



Outfeed belt scraper

The belt is kept clean throughout use.



Oil recycling system

Reduces oil consumption. Fitted with a filter and a low level alert.



Flour dispenser

JAC has developed a brand new, more efficient integrated flour dispenser with a more regulated flow. It now equips the GD and GDS series.

